



ENTRUST

Entrust Artista CR825 Instant Issuance System

HIGHLIGHTS

Surpass cardholder expectations with retransfer print technology

Whether your customers or members are opening a new account or replacing a card, they don't want to wait to use your product. Entrust instant issuance solutions – including the CR825 system – deliver permanent, high-quality cards the moment they're needed. Our retransfer technology enables customized card designs that:

- Can be created in minutes
- Have an immediate impact on your customers

Our system allows you to provide personalized products and services that are customized to meet the demands of your clientele. We offer a comprehensive, flexible solution with printing, encoding, and embossing now possible within one system.



SINGLE-HOPPER

KEY FEATURES & BENEFITS

Vibrant, permanent embossed cards that reflect your brand

- Produce permanent, durable cards using pigment inks, which naturally create longer-lasting images
- Over-the-edge retransfer color printing, combined with extreme precision printing capability, provides high-quality card imagery
- Optional second layer of retransfer film available to further enhance durability

A superior solution that makes financial sense

- Simplify card and inventory management, reduce storage needs, and lower preprinting costs by using blank card stock to print custom or standard cards on demand
- Matched supplies help ensure color ribbon and retransfer material are consumed at the same rate for efficient printer management



Entrust Artista CR825 Instant Issuance System

A wide range of capabilities to meet your needs

- Encode magnetic stripe, contact, and contactless EMV cards to ISO standards
- 600 dot per inch printing using pigment-based ink creates bright, vibrant colors, designs, and images that resist fading, unlike dye

Security you can rely on

- Dual-control access to protect card stock, supplies and rejected cards, meeting Visa and Mastercard security requirements
- SSL/TLS1.2 encryption protects sensitive data
- Secure Boot prevents system startup if malware is detected
- Securely insert, manage, and remove user-specific certificates and keys using the included TPM module

THE ENTRUST DIFFERENCE

Instant issuance solutions enable real-time, personalized service

Each element of our solution is built to create a seamless experience across our hardware, software, services, and supplies. With Entrust, you have one instant issuance partner to help you every step of the way.



Entrust Artista CR825 Instant Issuance System

FEATURES AND SPECIFICATIONS

Print technology

- Retransfer pigment ink

Print resolution

- 600 dots per inch (dpi)

Print speed

- Dual-sided (CMYKP-KPI):
up to 60 cards per hour

Print capabilities

- One- or two-sided printing
- Over-the-edge, full-card printing
- Full-color images

Color modes

- True Color (ICC) – prints colors of the image as defined in the card design
- Legacy SR/CR – close match to the CR500 Instant Issuance System
- Vivid – printer colors with higher saturation and contrast

Card capacity

- Card thickness: 0.030 inches (0.76 mm) – ISO ID1/CR-80
- Input hopper: Single removable hopper – Capacity 125 cards 0.030 inches (0.76 mm)
- Output hopper: Normal 25 cards; expandable kit to 125 cards
- (Optional) Multi-Hopper: Six-compartment multi-hopper; six 125-card hoppers; 750-card total capacity

Magnetic stripe encoding

- IAT/ISO magnetic stripe encoding
- Optional JIS magnetic stripe encoding
- HiCo/LoCo 1, 2, and 3 track encoding

EMV smart card encoding

- Ethernet and USB
- Single-wire connectivity
- Contact/Contactless read/write EMV encoding
- ISO 7816 T=0 & T=1
- ISO 14443 A/B

Security features

- SSL and TLS 1.2 encryption supports Triple DES and AES-128
- Electronic (through Entrust Financial Instant Issuance software) and mechanical locks (meets Visa and Mastercard requirements)
- Bolt-down provision for securing printer to work area
- TPM Module standard; utilize with Adaptive Issuance Instant Financial Issuance for secure location to insert, manage, and, remove user-specific certificates and keys
- Secure Boot prevents system startup if malware is detected
- Kensington style lock compatible (lock sold separately)
- Concealed output hopper

LCD display

- Displays printer status
- Access to printer settings

WiFi (Optional feature)

- Supports the following WiFi types: G (7 MB/s), N (100 MB/s)
- Supports the following Authentication Modes: None, WPA2, Personal
- Supports having WiFi using one network (SSID) and Ethernet wired connection
- Supports having WiFi using one network (SSID) and USB connection
- Supports dual-band 2.4GHz & 5GHz

Built-in card debowing feature with user-friendly operation

- Automatic card feed
- Quick-change ribbon cassettes
- Color-coded supplies

Warranties

- 36-month system warranty



Entrust Artista CR825 Instant Issuance System

Single Hopper

Physical dimensions (depth x width x height)

- 21.4 in x 10.1 in x 15.6 in
(54.36 cm x 25.65 cm x 39.62 cm)

Weight

- 28 lb. (12.7 kg); with options will vary

Multi-hopper

Physical dimensions

- L 21.4 in x W 10.1 in x H 15.6 in
L 54.34 cm x 25.53 cm x H 39.68 cm)

Weight

- 28 lbs. (12.7 kg); with options will vary

Connectivity

- Ethernet
- IPv4 and IPV6

Card types accepted

- ISO/CR-80 size
- 3.370 in. x 2.125 in. (85.60 mm x 53.98 mm)
- PaVC, PVC composites, PET, PET-G, Polycarbonate

Operating environment

- 60° F to 95° F (15° C to 35° C)
- 20% to 80% non-condensing humidity

Storage environment

- 5° F to 131° F (-15° C to 55° C)
- 20% to 80%, non-condensing humidity

Electrical requirements

(dual voltage, autosensing)

- 100/120 V, 50/60 Hz
- 220/240 V, 50/60 Hz

Supplies

Color ribbons

- CMYKP-KPi 500 images

Clear retransfer film: Two options:

- 1,000 images (single-sided), 500 images (dual-sided)
- 1,500 images (single-sided), 750 images (dual-sided)

Software Compatibility

Compatible with Entrust instant financial issuance software.



MULTI-HOPPER



www.elliottdata.com



*Local Identification, Secure Access
& Accountability Solutions Provider*

St. Louis, MO | Memphis, TN

1-888-345-8511