

DATASHEET

Entrust Datacard DS3 Direct-to-Card Printer

HIGHLIGHTS

Entrust Datacard: The Next Generation of Direct-to-Card Printing

Entrust® Datacard® (formerly Sigma) ID Card Printers are specifically designed for today's cloud environments and give you the ability to easily issue secure identities.

- **Simple:** From unboxing to issuing ID cards and mobile flashpasses to managing your printer, we made sure Datacard was the most user-friendly ID card issuance solution in the world
- **Secure:** Our industry-leading issuance security architecture will keep your cards and your customers' data safe and secure each step of the issuance process
- **Smart:** Forward-thinking technology and scalability allow you to expand your ID card program as your needs evolve



KEY FEATURES & BENEFITS

The World's Most User-Friendly ID Card Printer

- Intuitive printer dashboard lets you see printer status, order supplies, check cleaning status, update firmware, or contact help – all from your mobile device
- Seamless self-service lets you access how-to videos and other helpful resources by simply scanning a QR code on the LCD display
- Variable LED light ring lets you incorporate brand colors or other customization into your ambient environment
- Optional pre-loaded ribbon cassettes make switching ribbons easy
- Innovative patented printhead protector feature shields the printhead during ribbon replacement or printer servicing, which helps to extend the printhead life. Enables you to easily fix the issue at hand without having to worry about damaging the printhead.



ENTRUST
SECURING A WORLD IN MOTION

Unmatched Security

- UV printing and other security features added to the cards protect from tampering and counterfeiting
- Secure Boot cryptographically authenticates firmware, preventing printer operation if unauthorized modifications are detected
- Trusted Platform Module (TPM) secures a factory-installed Entrust-backed TLS certificate
- Network communication in accordance with NIST SP 800-52 Rev. 2 recommendations when using
- TLS 1.2 or 1.3 with strong cryptographic protocols*
- Zero Trust network support using RADIUS-enabled IEEE 802.1x password or certificate-based authentication
- Optional locks protect card stock and supplies
- Security features added to cards protect from tampering and counterfeiting:
 - UV printing
 - Holographic laminates
 - Luster printing

Flexibility and Scalability Built for the Future

- Issuance capabilities include physical cards and digital mobile flashpass
- Choose on-premises or cloud-hosted deployment
- Expand your ID program as your needs change by adding multi-hopper, smart card capabilities, color tactile printing, and more
- Print anytime, anywhere with your mobile device (iOS, Android, Windows)



ENTRUST
SECURING A WORLD IN MOTION

TECHNICAL SPECIFICATIONS

Standard Features & Supplies			
Print technology	Dye-sublimation / resin thermal transfer		
Print capabilities	Single- or dual-sided, rewritable technology		
Print resolution	300 dots per inch (dpi) (300 x 600, 300 x 1200)		
Print speed	Single-sided color ribbon: up to 250 cards per hour (cph) Double-sided color ribbon: up to 180 cards per hour (cph)		
Card capacity	Input hopper: 125 cards Output hopper: 25 cards		
Card sizes	Thickness: 0.010 inches to 0.040 inches (0.25mm - 1.016mm) Dimension: ID-1 (CR-79, CR-80) Reject hopper: 10 cards		
Operating environment	Temperature: 60°F to 95°F (15°C to 35°C) Humidity: 20-80% RH – non condensing		
Physical dimensions	L 17.4 in. x W 8.3 in. x H 9 in. / 44.2 cm x 22.1 cm x 22.9 cm		
Weight	12.1 lbs (5.49 kg); varies with options		
Connectivity	USB and Ethernet		
Warranty	36 months		
Web browser support for Instant ID as a Service	Chrome (preferred) Edge/Internet Explorer Safari		
Operating system support for printer driver	Windows 11 Windows 10, 32- and 64-bit	Windows Server 2019 Windows Server 2022	Linux Ubuntu 20.04 LTS Linux Kylin



Optional Features & Supplies

Magnetic stripe encoding	ISO 7811 three-track support (high- and low-coercivity) JIS Type II single-track option
Multi-hopper	Six compartment multi-hopper (six 125-card hoppers, 750-card total capacity)
WiFi	Standards: 802.11g/n/ac Frequencies: 2.4GHz & 5GHz Authentication modes: WPA2 Personal, WPA2 Enterprise
Smart card encoding*	Single wire or loosely coupled: • Contact smart card encoding: ISO 7816 T=0 (T=1), Class A 5V (3V and 1.8V) • Contactless smart card encoding: ISO 14443 A/B, ISO 15693, MIFARE, MIFARE DESFire EV1/EV2, HID Prox, iClass, iClass SE, iClass Seos, Felica
Color ribbons**	Prefilled print ribbon cassettes: YMCKT 500 images YMCKT-KT 350 images KTT 750 images WTT 650 images ST-KT 500 images GT-KT 500 images Refill print ribbon kits: YMCKT 250/500 images YMCKT 650 images YMCKT-KT 350 images YMCKT-KT 435 images KT 1,000 images KTT 750 Images WTT 650 images ST-KT 500 images YMCKF-KT 300 images YMCKL-KT 300 images
Monochrome ribbons	Black, white, blue, red, green, scratch-off, silver matte, gold matte, silver metallic, and gold metallic; 2,500 average images

*Compatibility with specific features of new card technologies should always be confirmed.

** Color ribbon guide: Y=Yellow, M=Magenta, C=Cyan, K=Black, T=Topcoat, F=UV fluorescent, L=Luster, y=1/2 panel Yellow, m=1/2 panel Magenta, c=1/2 panel Cyan, S=Silver matte, G=Gold matte, W=White.

Panel print ribbon yields stated are typically the maximum number of panel sets per roll.

Monochrome print ribbon yields stated at 2,500 are the estimated image yield for industry average personalization of 1.



*Local Identification, Secure Access
& Accountability Solutions Provider*

St. Louis, MO | Memphis, TN

1-888-345-8511